

## RANGE OF EXTERNAL HOUSINGS

### Model: VCMH Series

#### FULL AND SEMI CABLE MANAGED EXTERNAL CAMERAS

Conforming to an impressive IP66 rating, each unit in the VCMH range is pre-treated with an extremely durable marine weatherproof epoxy coating. As a result you can rest assured that the housing and its valuable contents will remain protected, even in the most hostile of environmental conditions. The same protective coating will also prevent UV radiation damage to your surveillance equipment.

However, despite its extremely tough exterior, the VCMH range has been thoughtfully designed to maximize ease of installation and subsequent maintenance. The top of the housing, when unsecured, slides forward and then hangs below the housing body, giving you maximum accessibility to the camera inside without having to remove the sunshield. The unit also features an integral bracket, allowing totally discreet cable management to be achieved.

All units come with an integral heater and thermostat to monitor changes in weather conditions, as well as a separate aluminum sun shield to ensure that the housing is kept cool when external temperatures rise.



VCMHF



VSCMH250

### Key Features:

#### Marine Finish with IP66 rating

This makes the housing suitable for coastal installations and harsh environments

#### Slide and Hang housing

This makes for easier access to the housing to make installation and servicing easier

#### Wall Mounting

With a choice of integral semi cable managed and fully cable managed wall brackets, the housing can be used in a wide variety of applications

THE PROFESSIONAL CHOICE

## TECHNICAL SPECIFICATION:

|                                                        | VCMH                  | VCMHF | VCMHF/B | VCMH24F | VSCMH   | VSCMHF | VSCMH250        | VSCMH250/LV  | VSCMH24F        | VCMH250         |
|--------------------------------------------------------|-----------------------|-------|---------|---------|---------|--------|-----------------|--------------|-----------------|-----------------|
| IP Rating                                              | IP66                  |       |         |         |         |        |                 |              |                 |                 |
| Opening                                                | Slide and Hang        |       |         |         |         |        |                 |              |                 |                 |
| Cable Management                                       | Yes                   |       |         |         | No      |        |                 |              |                 | Yes             |
| Colour                                                 | RAL7035               |       | Black   | RAL7035 |         |        |                 |              |                 |                 |
| Construction                                           | Epoxy Coated Aluminum |       |         |         |         |        |                 |              |                 |                 |
| Heater Voltage                                         | 240V AC               |       |         | 24V AC  | 240V AC |        |                 | 12-24V AC/DC | 24V AC          | 240V AC         |
| Power Consumption                                      | 30W                   |       |         |         |         |        |                 |              |                 |                 |
| Weight                                                 | 4.5Kg                 |       |         |         | 5Kg     |        | 4Kg             |              | 4.5Kg           | 4Kg             |
| External Dimensions<br>Excluding Bracket<br>(LxWxH) mm | 445 x 180 x 130       |       |         |         |         |        | 410 x 125 x 120 |              | 445 x 180 x 130 | 410 x 125 x 120 |
| Max. Camera and Lens<br>Length (LxWxH) mm              | 305 x 105 x 86        |       |         |         |         |        | 250 x 75 x 70   |              | 305 x 105 x 86  | 250 x 75 x 70   |
| Fan                                                    | -                     |       |         |         |         |        |                 |              |                 | Yes             |

Note: Design & Specification are subject to change without prior notice.

## ASSOCIATED PRODUCTS:

|         |             |                                                               |
|---------|-------------|---------------------------------------------------------------|
| 0032800 | VCMHF       | Full cable managed flat sided housing, IP66, 240V AC          |
| 0325300 | VCMHF/B     | Full cable managed flat sided black housing, IP66, 240V AC    |
| 0033070 | VCMH24F     | Full cable managed flat sided external housing, IP66, 24V AC  |
| 0032810 | VSCMHF      | Semi cable managed flat sided external housing, IP66, 240V AC |
| 0033610 | VSCMH250    | Semi cable managed external housing, IP66, 240V AC            |
| 0092150 | VSCMH250/LV | Semi cable managed external housing, IP66, 12V DC or 24V AC   |
| 0032440 | VCMH        | Full cable managed housing, IP66, 240V AC                     |
| 0032410 | VSCMH       | Semi cable managed housing, IP66, 240V AC                     |
| 0033080 | VSCMH24F    | Semi cable managed flat sided external housing, IP66, 24V AC  |
| 0033590 | VCMH250     | Full cable managed external housing, IP66, 240V AC            |
| 0342560 | HT6/LV      | Low voltage heater                                            |
| 0342580 | HT6/MAINS   | Mains heater                                                  |
| 0032830 | VPA1        | Single housing pole adapter                                   |
| 0032700 | VPA2        | Dual housing pole adapter                                     |