

22" LED MONITOR

Model: VL-22WBC



Features:

- More pixel optional, support signal input 4K and 1080P, more suitable for 4K DVR or NVR use.
- Automatically detect the resolution of the input signal in the upper right corner of the screen when it is turned on.
- Clear: Delicate and realistic, conveys true colors, and shows truly color.
- Bright: The picture quality is improved, just for better presentation.
- Using industrial screen, high brightness, high contrast.
- Adopt high-precision standard regulated power supply, specially designed for industrial equipment, support 24 hours x 365 days of uninterrupted work.
- It adopts semi-metal shell, strong structure, fire-proof, moisture-proof and shock-proof, especially suitable for equipment that is easily affected by electromagnetic interference.
- Using 8bit image chip processing technology, high-pixel progressive scanning, the picture quality is exquisite.
- Supports intelligent 3D noise reduction, afterimage removal, dynamic brightness, contrast and color optimization technology.
- Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality.
- The liquid crystal has small size, low energy consumption, zero radiation, stable image, no effect on eyes, natural health.
- 6ms ultra-fast response, avoiding the smearing phenomenon of the image in high-speed operation.
- Using nanotechnology, the picture is more three-dimensional and transparent.

Specification:

PANEL PARAMETERS	
Panel Size	22" TFT LED
Resolution	1920 X 1080 (compatible with 4K signal input)
Aspect Ratio	16:9
Brightness	300 cd/m ²
Contrast	3000:1
Visual angle	178° (H)/178° (V)
Response Time	6ms
Color	16.7M (8-bit)
INPUT INTERFACE	
Video Input	RCA x 3
VGA Input	VGA x 1
HDMI input	HDMI x 1
USB port	USB x 1
Audio	Output Jack
OPERATING ENVIRONMENT	
Working Temperature	0 C ~ 50 C
Storage Temperature	-20C ~ 60C
Working humidity	5% ~ 90%
POWER CONSUMPTION	
Power Supply	DC 12V External Adaptor
Power Consumption	<50W
Standby Consumption	<1W
Dimension	510 mm × 320 mm × 60 mm (20.1" × 12.6" × 2.4")
Net Weight	3.8 kg
INDUSTRY STANDARDS	
Quality Standard	China 3C certification, China energy saving certification, patent certificate, copyright, authoritative test report
Environmental Standard	All components and packing accessories comply with international environmental standards
Installation Method	Desktop base, wall mount, suspending mount
Wall mount hole	100x100
Menu Language	Supports 20 Languages
Housing Color	Black
Housing Material	ABS; support HDMI audio with output jack; built-in temperature monitoring warning

Note: Design & Specification are subject to change without prior notice.

VIDEOLINEUSA Security Systems, Inc.

Head Office : 601, Woolim e-BizII,
184-1 Guru Dong, Guru-gu,
Seoul 152-050, Korea
Tel # : +82-2-8913231
Fax # : +82-2-856-8732
Email : info@videolineusa.com